

## You Ji Vertical Turning Centers Specifications\*

MODEL	MAX. SWING	MAX. CUTTING DIAMETER	MAX. CUTTING HEIGHT	CHUCK SIZE	TURRET TOOLS	SPINDLE HP	RPM	C-AXIS	TWIN SPINDLE	WEIGHT
YV-200B	15.7"	10"	8"	8"	Gang	15	4,000 RPM	No	Optional	6,600 lb.
YV-200E	15.7"	10"	8"	8"	8 Drum	15	4,000 RPM	Optional	Optional	6,600 lb.
YV-320A	23.6"	17.7"	10"	12"/15"	6 Hex	25	2,100 RPM	No	Optional	13,200 lb.
YV-320B	23.6"	17.7"	10"	12"/15"	Gang	25	2,100 RPM	No	Optional	13,200 lb.
YV-320C	23.6"	17.7"	10"	12"/15"	10	25	2,100 RPM	Optional	Optional	13,200 lb.
YV-320E	23.6"	17.7"	10"	12"/15"	8 Drum	25	2,100 RPM	Optional	Optional	13,200 lb.
YV-500A	31"	31"	25.6"	15"/24"	6 Hex	50+2-Speed	2,000 RPM	No	Optional	22,000 lb.
YV-500E	31"	31"	25.6"	15"/24"	10 Drum	50+2-Speed	2,000 RPM	Optional	Optional	22,000 lb.
YV-600A	33.5"	33.5"	25.6"	24"/32"	6 Hex	50+2-Speed	1,500 RPM	No	Optional	30,800 lb.
YV-600E	33.5"	33.5"	25.6"	24"/32"	10 Drum	50+2-Speed	1,500 RPM	Optional	Optional	30,800 lb.
YV-600ATC	33.5"	33.5"	25.6"	24"/32"	12 ATC	50+2-Speed	1,500 RPM	Optional	Optional	30,800 lb.
YV-800A	48"	40"	31.5"	24"/40"	6 Hex	50+2-Speed	800 RPM	No	Optional	33,000 lb.
YV800E	48"	40"	31.5"	24"/40"	10 Drum	50+2-Speed	800 RPM	Optional	Optional	33,000 lb.
YV-800ATC	48"	40"	31.5"	24"/40"	12 ATC	50+2-Speed	800 RPM	Optional	Optional	33,000 lb.

### STANDARD ACCESSORIES:

- 1 CHIP CONVEYOR
- 2 FULL MACHINE ENCLOSURE
- 3 3 JAW HYDRAULIC POWER CHUCKS
- 4 FANUC CNC CONTROL

\* All data subject to change without notice